

### 概述 Summary

- > 单组输出; 功率60W  
Single output: power 60W
- > 输入电压: 85 ~ 264VAC 120 ~ 370VDC  
Input voltage: 85 ~ 264VAC 120 ~ 370VDC



### 常见规格 General Specification

78 × 93 × 56mm

性能 Specification	型号 Model	DR-60-5	DR-60-12	DR-60-15	DR-60-24
直流输出电压、电流 DC output voltage, current		5V 0~6.5A	12V 0~4.5A	15V 0~4A	24V 0~2.5A
纹波及噪音 Wave and noise		80mVp-p	120mVp-p	120mVp-p	150mVp-p
进线稳定度 Inlet wire stability		± 0.5%	± 0.5%	± 0.5%	± 0.5%
负载稳定度 Load stability		± 1%	± 0.5%	± 0.5%	± 0.5%
效率 Efficiency		76%	82%	83%	84%
直流电压可调范围 Adjustable range for DC voltage		± 10%	± 10%	± 10%	± 10%
输入电压范围 Input voltage range		85 ~ 264VAC 120 ~ 370VDC 47 ~ 63Hz			
冲击电流 Impact current		冷启动电流 18A/115VAC 36A/230VAC Cold start current			
过载保护 Overload protection		105% ~ 160%切断输出, 自动恢复 105% ~ 160% cut off the output, automatic recovery			
过电压保护 Over voltage protection		115% ~ 135%关闭输出, 电源重启后可恢复输出 115% ~ 135% shut down O/P voltage, re-power on to recover			
启动、上升、保持时间 Setup, rise, hold up time		800ms, 60ms, 50ms/230VAC 满负载 at full load			
耐压性 Withstand voltage		输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ			
工作温度 Working temperature		-10°C ~ +50°C			
尺寸 Dimension		78 × 93 × 56mm			
重量 Weight		0.3kg			
包装 Packing		43 × 32 × 21.5CM/45PCS/13.5kg			

### 外形尺寸 Overall dimension(mm)

- ☒ 接线位置
- ☒ 端口 1,2 : 交流输入
- ☒ 端口 3,4 : 直流输出+V
- ☒ 端口 5,6 : 直流输出-V
- ☒ Terminal Pin No. Assignment
- ☒ Pin 1,2 : AC input
- ☒ Pin 3,4 : DC output+V
- ☒ Pin 5,6 : DC output-V

