

S-75W单组输出电源 S-75W Single output power supply

概述 Summary

- > 单组输出：功率75W
Single output: power 75W
- > 输入电压：90 ~ 132VAC/180 ~ 264VAC 由开关切换
Input voltage: 90 ~ 132VAC/180 ~ 264VAC by switch



常见规格 General Specification

159 × 98 × 38mm

性能 Specification	型号 Model	S-75-12	S-75-15	S-75-24	S-75-48
直流输出电压、电流 DC output voltage, current		12V 0~6A	15V 0~5A	24V 0~3.2A	48V 0~1.5A
纹波及噪音 Wave and noise		100mVp-p	100mVp-p	120mVp-p	150mVp-p
进线稳定度 Inlet wire stability		± 0.5%	± 0.5%	± 0.5%	± 0.5%
负载稳定度 Load stability		± 0.5%	± 0.5%	± 0.5%	± 0.5%
效率 Efficiency		78%	79%	82%	83%
直流电压可调范围 Adjustable range for DC voltage		± 10%	± 10%	± 10%	± 10%
输入电压范围 Input voltage range		90 ~ 132VAC/180 ~ 264VAC 由开关切换 254 ~ 370VDC 47 ~ 63Hz 90 ~ 132VAC/180 ~ 264VAC by switch 254 ~ 370VDC 47 ~ 63Hz			
冲击电流 Impact current		冷启动电流 Cold start current 15A/115VAC 30A/230VAC			
过载保护 Overload protection		105% ~ 150%切断输出，自动恢复 105% ~ 150% cut off the output, automatic recovery			
过电压保护 Over voltage protection					
启动、上升、保持时间 Setup, rise, hold up time		200ms, 50ms, 20ms/230VAC 满负载 at full load			
耐压性 Withstand voltage		输入输出间：1.5kV 输入与外壳间：1.5kV 输出与外壳间：0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间：500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ			
工作温度 Working temperature		-10°C ~ +50°C			
尺寸 Dimension		159 × 98 × 38mm			
重量 Weight		0.55kg			
包装 Packing		34 × 32 × 24CM/30PCS/16.5kg			

外形尺寸 Overall dimension(mm)

- 接线位置
- 端口 1,2: 交流输入
- 端口 3: 接地
- 端口 4: 直流输出-V
- 端口 5: 直流输出+V
- Terminal Pin No. Assignment
- Pin 1,2: AC input
- Pin 3: GND
- Pin 4: DC output-V
- Pin 5: DC output+V

